

Size	18.4"
Resolution	3840 x 2160 (16:9)
Pixel Pitch	0.03555(H) x 0.1065(V) mm
Color Depth	1.07B Colors
Viewing Angle	170°(H) / 170°(V)
Luminance of white	1000nits
Contrast Ratio	1000 : 1
Display Area	408.96(H) x 230.04(V) mm

Input

4 x BNC	12G/6G/3G/HD-SDI A/B, 3G/HD-SDI C/D Channel Input
1 x HDMI	HDMI(2.0) Input

Output

4 x BNC	12G/6G/3G/HD-SDI A/B, 3G/HD-SDI C/D Channel (Active Through Out)
---------	--

Input Signal

12G-SDI	12Gb/s
6G-SDI	6Gb/s
3G-SDI	2.970Gb/s
HD-SDI	1.485Gb/s
HDMI	2160p(60)/1080p(60)/1080i(60)/720p(60)/480i(60)/480p(60)/576i(50)/576p(50)

SDI Input Signal Formats

SMPTE ST 2082	3840x2160 (60/50/30/25/24p)
SMPTE ST 2081	3840x2160 (30/25/24p)
SMPTE ST 2036-1:2009	3840x2160(23.98/24/25/29.97/30/50/59.94/60p)
SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	1080i(60/59.94/50)
SMPTE-274M	1080i (60/59.94/50)
	1080p (30/29.97/25/24/24sF/23.98/23.98sF)
SMPTE-296M	720p(60/59.94/50)
SMPTE-260M	1035i (60/59.94)
SMPTE-125M	480i (59.94)
ITU-R BT.656	576i (50)
SMPTE ST 2048-2:2011	2048x1080(23,98/24/25/29.97/30p/psf, 47.95/48/50/59.94/60p)

Audio In	Embedded Audio Analog Stereo(Phone Jack)
Audio Out	Internal Speaker(Stereo) Analog Stereo(Phone Jack)
Power	DC 12V / 24V / AC 100~240V(50~60Hz)
Power Consumption (Approx.)	85Watts
Included Accessories	AC Power Cord, Table Stand, Control Knob Cap, Carry Handle