

S-46P-N

LCD	Size	46"
	Resolution	1920 x 1080 (16:9)
	Pixel Pitch	0.5302(H) x 0.5302(W) mm
	Color Depth	1.073B Colors (10bit)
	Viewing Angle (Typ.)	178°(H) / 178°(V)
	Luminance of white	500cd/m2
	Contrast Ratio	4000 : 1
	Display Area	1018.08(H) x 572.67(V) mm
Input	2 x BNC	12G/6G/3G/HD/SD-SDI A/B Input
	3 x BNC	YPbPr, CVBS Input
	1 x HDMI	HDMI 1.4 Input
	2 x SFP	SFP A/B Channel Input
	1 x BNC	Reference Input
Output	2 X BNC	12G/6G/3G/HD/SD-SDI A/B Channel Output
	3 X BNC	YPbPr, CVBS Output
	1 X BNC	Processed Output
SDI Input Signal Formats	SMPTE ST 2082	3840x2160 (60/50/30/25/24p)
	SMPTE ST 2081	3840x2160 (30/25/24p)
	SMPTE ST 2036-1:2009	3840x2160 (23.98/24/25/29.97/30/50/59.94/60p)
	SMPTE-425M-A/B	1080p (60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
		1080i (60/59.94/50)
	SMPTE-274M	1080i (60/59.94/50)
		1080p (30/29.97/25/24/24sF/23.98/23.98sF)
	SMPTE-296M	720p (60/59.94/50)
	SMPTE-260M	1035i (60/59.94)
	SMPTE-125M	480i (59.94)
	ITU-R BT.656	576i (50)
	SMPTE ST 2048-2:2011	2048x1080 (23.98/24/25/29.97/30p/psf, 47.95/48/50/59.94/60p)
Remote Control & Update	1 x LAN	RJ-45 Input(Ethernet), Firmware Update & Remote Control
	1 x REMOTE	RJ-45 Input, GPI Control
	2 x RS-422	RJ-45 Input & Output, Monitor Control by TVLogic Protocol or TSL Protocol
	1 x USB	USB A type, Firmware Update
Audio	Audio In	Analog Stereo (3.5mm Phone Jack)
	Audio Out	Analog Stereo (3.5mm Phone Jack)
General	Power	AC100~240V(50~60Hz)
	Power Consumption	TBD
	Operating Temperature	0°C to 35°C (32°F to 95°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
	Dimensions: Main Body	1070.6 x 637.5 x 76.4 mm / 42.15 x 25.09 x 3.00 inch
	Dimensions: With Stand	1070.6 x 686.4 x 245.0 mm / 42.15 x 27.02 x 9.65 inch
	Dimensions: Shipping Box	1270 x 410 x 950 mm / 50.00 x 16.14 x 37.40 inch
	Weight (with stand)	26.3kg / 57.98lbs
	Basic Accessories	AC Power Cord, Stand
	Optional Accessories	-

*The specifications above may be changed without notice.