

Specifications		S-55P
LCD	Size	55"
	Resolution	1920 x 1080 (16:9)
	Pixel Pitch	0.63(H) x 0.63(W) mm
	Color Depth	1.073B (10bit)
	Viewing Angle (Typ.)	178°(H) / 178°(V)
	Luminance (Max.)	450 cd/m2 (Max)
	Contrast Ratio	4000 : 1
	Display Area	1209.6(H) X 680.4(V) mm
Input	2 x BNC	SDI Input
	2 x SFP	Input/Output (Combined)
	1 x HDMI	HDMI Input
	1 x DVI-D	DVI Input
Output	2 x BNC	SDI Output
Input Signal	3G-SDI	2.970Gb/s
	HD-SDI	1.485Gb/s
	SD-SDI	270Mb/s
	DVI	VESA/IBM Modes
	HDMI	1080p(60/59.94/50/30/25/24/23.98)/1080i(60/59.94/50)/720p(60/50)/480i(60)/480p(60)/576i(50)/576p(50)
SDI/SFP Input Signal Formats	SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/30sF/29.97sF/25sF/24sF/23.98sF)
	SMPTE-274M	1080i(60/59.94/50)
		1080p(30/29.97/25/24/24sF/23.98/23.8sF)
	SMPTE-296M	720p(60/59.94/50)
	SMPTE-125M	480i(59.94)
ITU-R BT.656	576i(50)	
Audio	Embedded Audio / Analog Stereo Out (Phone Jack)	
Power	AC100~240V (50~60Hz)	
Power Consumption (Approx.)	110W	
Operating Temperature	0°C to 45°C (32°F to 113°F)	
Storage Temperature	-20°C to 60°C (-4°F to 140°F)	
Dimensions	Main Body (mm/inch)	1262.0 x 736.0 x 76.4(mm) / 49.68 x 28.97 x 3.00(inch)
	With Stand (mm/inch)	1262.0 x 784.5 x 254(mm) / 49.68 x 30.88 x 9.65(inch)
	Shipping Box (mm/inch)	1410 x 410 x 1050(mm) / 55.51 x 16.14 x 41.34(inch)
Weight	With Stand	31.8kg / 70.1lbs
Accessory	Basic	AC Power Cord, Remote Control, USB Cover, Stand
	Optional	SFP Module

\*The specifications above may be changed without notice.